

Taxi Regulations

Minimum Wheelchair Space	700 mm width 1,200 mm length 1,350 mm headroom	700 mm width 1,200 mm length 1,350 mm headroom
Door (Min 1 Wheelchair Accessible Door)	750 mm width 1,235 mm high, One other door also available.	745 mm width 1,250 mm high, One other door also available.
External Step at Nearside Door.	The passenger step height at one of the nearside entrances must not exceed 380 mm; where it's a step, it must be not less than 200mm deep and 400 mm wide.	If lowest foothold is more than 230 mm from ground and door is wider than 1.150 mm, access step is required,
Ramp	Surface must be continuous in width. Angle to kerb must be less than 16%. SWE of 300kg min. If detachable, must have safe storage and be marked with Vehicle Reg.	When deployed, Surface must be one piece. Angle to kerb must be less than 16%. SWE of 300kg min. If detachable, must have safe storage and be marked with Vehicle Reg.
Wheelchair Restraint	ISO approved 4 point restraint system with labelling and seat to floor strength test.	ISO approved 4 point restraint system with labelling and seat to floor strength test.
Passenger Restraint	ISO approved 3 point restraint system with labelling and strength test.	ISO approved 3 point restraint system with labelling and strength test.
Other Requirements	For a more comprehensive list, please see "Initial Suitability Inspection Manual"	For a more comprehensive list, please see "Initial Suitability Inspection Manual"